

**Description**

grip range: 0.010" - 0.080", thread: 10-32, flat head, aluminum alloy, NAS132 series nut

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1329A380
Minimum Qty (MOQ):	50
NSN:	5310-00-052-7528
Schedule B:	7616.10.9090
ECCN:	EAR99
National Motor Freight:	013540, Alum Nuts



## P/N NAS1329A3-80 Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Head Style:</b>	Flat
<b>Head Diameter:</b>	0.406 Inches Nominal
<b>Head Height:</b>	0.038 Inches Nominal
<b>Nut Style:</b>	Blind Rivet W/smooth Round Shank
<b>Nut Diameter:</b>	0.250 Inches Nominal
<b>Nut Length:</b>	0.516 Inches Minimum And 0.546 Inches Maximum
<b>Err Default:</b>	+0.010/+0.080 Inches
<b>Unable To Decode:</b>	+0.010 To 0.080 Inches
<b>Shank End Type:</b>	Open
<b>Thread Series:</b>	Unf
<b>Thread Quantity Per Inch:</b>	32
<b>Nominal Thread Size:</b>	0.190 Inches
<b>Material:</b>	Aluminum Alloy 3003 Overall Or Aluminum Alloy 6053 Overall Or Aluminum Alloy 6061 Overall
<b>Material Document And Classification:</b>	Mil-a-1150 Mil Spec All Material Responses Overall
<b>Surface Treatment:</b>	Anodize Overall
<b>Specification/standard Data:</b>	80205-nas1329 Professional/industrial Association Standard

## How to Order

Order this plain blind rivet nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1329A3-80> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.