

Description

keyed grip range: 0.130" - 0.180", thread: 10-32, blind rivet nut, flat head - aluminum alloy

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[MS27130A27K](#)

SKU / Model:	NAS1329A3K180
Minimum Qty (MOQ):	25
NSN:	5310-00-177-7529
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS1329A3K180 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Head Style:	Flat Keyed
Head Diameter:	0.391 Inches Minimum And 0.421 Inches Maximum
Key Length:	0.061 Inches Nominal
Head Height:	0.038 Inches Nominal
Nut Style:	Blind Rivet W/smooth Round Shank
Nut Diameter:	0.246 Inches Minimum And 0.250 Inches Maximum
Nut Length:	0.626 Inches Minimum And 0.656 Inches Maximum
Err Default:	+0.130/+0.180 Inches
Unable To Decode:	+0.130 To 0.180 Inches
Shank End Type:	Open
Thread Series:	Unf
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.190 Inches
Material:	Aluminum Alloy Overall
Material Document And Classification:	Mil-r-1150 Mil Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625,ty 2 Mil Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1329 Professional/Industrial Association Standard

How to Order

Order this plain blind rivet nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1329A3K180> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.