

**Description**

keyed grip range: 0.130" - 0.180", thread: 10-32, blind rivet nut, flat head - aluminum alloy

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[MS27130A27K](#)

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS1329A3K180                             |
| Minimum Qty (MOQ):      | 25  |
| NSN:                    | 5310-00-177-7529                          |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



\* See page 2 for technical characteristics

## P/N NAS1329A3K180 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3b   |
| <b>Thread Direction:</b>                              | Right-hand   |
| <b>Head Style:</b>                                    | Flat Keyed   |
| <b>Head Diameter:</b>                                 | 0.391 Inches Minimum And 0.421 Inches Maximum              |
| <b>Key Length:</b>                                    | 0.061 Inches Nominal                                       |
| <b>Head Height:</b>                                   | 0.038 Inches Nominal                                       |
| <b>Nut Style:</b>                                     | Blind Rivet W/smooth Round Shank                           |
| <b>Nut Diameter:</b>                                  | 0.246 Inches Minimum And 0.250 Inches Maximum              |
| <b>Nut Length:</b>                                    | 0.626 Inches Minimum And 0.656 Inches Maximum              |
| <b>Err Default:</b>                                   | +0.130/+0.180 Inches                                       |
| <b>Unable To Decode:</b>                              | +0.130 To 0.180 Inches                                     |
| <b>Shank End Type:</b>                                | Open   |
| <b>Thread Series:</b>                                 | Unf  |
| <b>Thread Quantity Per Inch:</b>                      | 32   |
| <b>Nominal Thread Size:</b>                           | 0.190 Inches   |
| <b>Material:</b>                                      | Aluminum Alloy Overall                                     |
| <b>Material Document And Classification:</b>          | Mil-r-1150 Mil Spec Single Material Response Overall       |
| <b>Surface Treatment:</b>                             | Anodize Overall  |
| <b>Surface Treatment Document And Classification:</b> | Mil-a-8625,ty 2 Mil Spec Single Treatment Response Overall |
| <b>Specification/standard Data:</b>                   | 80205-nas1329 Professional/industrial Association Standard |

## How to Order

Order this plain blind rivet nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1329A3K180> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.