

**Description**

Thread Size: 3/16", Nut Length: 47/64

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1329A3K230
Minimum Qty (MOQ):	50
NSN:	5310-00-021-7109
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013540, Alum Nuts



## P/N NAS1329A3K230 Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Head Style:</b>	Flat Keyed
<b>Head Diameter:</b>	0.406 Inches Nominal
<b>Key Length:</b>	0.061 Inches Nominal
<b>Head Height:</b>	0.038 Inches Nominal
<b>Nut Style:</b>	Blind Rivet W/smooth Round Shank
<b>Nut Diameter:</b>	0.250 Inches Nominal
<b>Nut Length:</b>	0.741 Inches Nominal
<b>Err Default:</b>	+0.180/+0.230 Inches
<b>Unable To Decode:</b>	+0.180 To 0.230 Inches
<b>Shank End Type:</b>	Open
<b>Thread Series:</b>	Unf
<b>Thread Quantity Per Inch:</b>	32
<b>Nominal Thread Size:</b>	0.190 Inches
<b>Material:</b>	Aluminum Alloy 6053 Overall
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Anodize Overall
<b>Specification/standard Data:</b>	80205-nas1329 Professional/Industrial Association Standard

## How to Order

Order this plain blind rivet nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1329A3K230> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.