

Description

Thread Size: 3/16", Nut Length: 47/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-------------------|
| SKU / Model: | NAS1329A3K230 |
| Minimum Qty (MOQ): | 50 |
| NSN: | 5310-00-021-7109 |
| Schedule B: | 7616.10.3000 |
| ECCN: | EAR99 |
| National Motor Freight: | 013540, Alum Nuts |



* See page 2 for technical characteristics

P/N NAS1329A3K230 Specifications

| | |
|--|--|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Head Style: | Flat Keyed |
| Head Diameter: | 0.406 Inches Nominal |
| Key Length: | 0.061 Inches Nominal |
| Head Height: | 0.038 Inches Nominal |
| Nut Style: | Blind Rivet W/smooth Round Shank |
| Nut Diameter: | 0.250 Inches Nominal |
| Nut Length: | 0.741 Inches Nominal |
| Err Default: | +0.180/+0.230 Inches |
| Unable To Decode: | +0.180 To 0.230 Inches |
| Shank End Type: | Open |
| Thread Series: | Unf |
| Thread Quantity Per Inch: | 32 |
| Nominal Thread Size: | 0.190 Inches |
| Material: | Aluminum Alloy 6053 Overall |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Overall |
| Surface Treatment: | Anodize Overall |
| Specification/standard Data: | 80205-nas1329 Professional/industrial Association Standard |

How to Order

Order this plain blind rivet nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1329A3K230> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.