

Description

Thread Size: 3/16", Nut Length: 3/4

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1329A3K280
Minimum Qty (MOQ):	25
NSN:	5310-00-682-0775
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013540, Alum Nuts



* See page 2 for technical characteristics

P/N NAS1329A3K280 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Head Style:	Flat Keyed
Head Diameter:	0.406 Inches Nominal
Key Length:	0.061 Inches Nominal
Head Height:	0.038 Inches Nominal
Nut Style:	Blind Rivet W/smooth Round Shank
Nut Diameter:	0.250 Inches Nominal
Nut Length:	0.750 Inches Nominal
Err Default:	+0.230/+0.280 Inches
Unable To Decode:	+0.230 To 0.280 Inches
Shank End Type:	Open
Thread Series:	Unf
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.190 Inches
Material:	Aluminum Alloy 6053 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Specification/standard Data:	80205-nas1329 Professional/Industrial Association Standard

How to Order

Order this plain blind rivet nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1329A3K280> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.