

**Description**

Thread Size: 3/16", Nut Length: 39/64"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |                                       |
|-------------------------|---------------------------------------|
| SKU / Model:            | NAS1329A3KB130                        |
| Minimum Qty (MOQ):      | 10 EA                                 |
| NSN:                    | 5310-00-058-1738                      |
| Schedule B:             | 7616.10.3000                          |
| ECCN:                   | 9A991                                 |
| National Motor Freight: | 077140, Fruits Dried / Evaporated Noi |

NO IMAGE  
AVAILABLE

## P/N NAS1329A3KB130 Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>                                  | 3b  |
| <b>Thread Direction:</b>                              | Right-hand  |
| <b>Head Style:</b>                                    | Flat Keyed  |
| <b>Head Diameter:</b>                                 | 0.391 Inches Minimum And 0.421 Inches Maximum   |
| <b>Key Length:</b>                                    | 0.061 Inches Nominal  |
| <b>Head Height:</b>                                   | 0.038 Inches Nominal  |
| <b>Nut Style:</b>                                     | Blind Rivet W/smooth Round Shank  |
| <b>Nut Diameter:</b>                                  | 0.246 Inches Minimum And 0.250 Inches Maximum   |
| <b>Nut Length:</b>                                    | 0.579 Inches Minimum And 0.609 Inches Maximum   |
| <b>Err Default:</b>                                   | +0.080/+0.130 Inches  |
| <b>Unable To Decode:</b>                              | +0.080 To 0.130 Inches  |
| <b>Shank End Type:</b>                                | Closed  |
| <b>Thread Series:</b>                                 | Unf   |
| <b>Thread Quantity Per Inch:</b>                      | 32  |
| <b>Nominal Thread Size:</b>                           | 0.190 Inches  |
| <b>Material:</b>                                      | Aluminum Alloy 3003 Overall Or Aluminum Alloy 6053 Overall Or Aluminum Alloy 6061 Overall |
| <b>Material Document And Classification:</b>          | Mil-a-1150 Mil Spec All Material Responses Overall  |
| <b>Surface Treatment:</b>                             | Anodize Overall   |
| <b>Surface Treatment Document And Classification:</b> | Mil-a-8625 Mil Spec Single Treatment Response Overall                                     |
| <b>Specification/standard Data:</b>                   | 80205-nas1329 Professional/industrial Association Standard                                |

## How to Order

Order this rivnut from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1329A3KB130> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.