

P/N NAS1329A3KB230

Description

Thread Size: 3/16", Nut Length: 61/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS1329A3KB230

Minimum Qty (MOQ): 10 EA

NSN: 5310-00-127-7354

Schedule B: 7616.10.3000

ECCN: 9A991

National Motor Freight: 077140, Fruits Dried / Evaporated Noi



^{*} See page 2 for technical characteristics

P/N NAS1329A3KB230 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Head Style:	Flat Keyed
Head Diameter:	0.391 Inches Minimum And 0.421 Inches Maximum
Key Length:	0.061 Inches Nominal
Head Height:	0.038 Inches Nominal
Nut Style:	Blind Rivet W/smooth Round Shank
Nut Diameter:	0.246 Inches Minimum And 0.250 Inches Maximum
Nut Length:	0.938 Inches Minimum And 0.968 Inches Maximum
Err Default:	+0.180/+0.230 Inches
Unable To Decode:	+0.180 To 0.230 Inches
Shank End Type:	Closed
Thread Series:	Unf
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.190 Inches
Material:	Aluminum Alloy 6053 Overall
Material Document And Classification:	Mil-r-1150 Mil Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625,ty 2 Mil Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1329 Professional/industrial Association Standard

How to Order

Order this rivnut from our inventory online by visiting https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1329A3KB230 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.