

Description

Thread Size: 1/4", Nut Length: 3/4

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1329A4K200
Minimum Qty (MOQ):	50
NSN:	5310-00-886-5829
Schedule B:	7616.10.1000
ECCN:	EAR99
National Motor Freight:	013540, Alum Nuts



* See page 2 for technical characteristics

P/N NAS1329A4K200 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Head Style:	Flat Keyed
Head Diameter:	0.460 Inches Minimum And 0.490 Inches Maximum
Key Length:	0.093 Inches Nominal
Head Height:	0.058 Inches Nominal
Nut Style:	Blind Rivet W/smooth Round Shank
Nut Diameter:	0.328 Inches Minimum And 0.332 Inches Maximum
Nut Length:	0.735 Inches Minimum And 0.765 Inches Maximum
Err Default:	+0.140/+0.200 Inches
Shank End Type:	Open
Thread Series:	Unf
Thread Quantity Per Inch:	28
Nominal Thread Size:	0.250 Inches
Material:	Aluminum Alloy 6061 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625,ty 2 Mil Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1329 Professional/industrial Association Standard

How to Order

Order this plain blind rivet nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1329A4K200> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.