

Description

Thread Size: 3/8", Nut Length: 1-25/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1329A6B200
Minimum Qty (MOQ):	5 EA
NSN:	5310-00-151-5434
Schedule B:	7616.10.1000
ECCN:	9A991
National Motor Freight:	013540, Alum Nuts



* See page 2 for technical characteristics

P/N NAS1329A6B200 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Head Style:	Flat
Head Diameter:	0.766 Inches Minimum And 0.796 Inches Maximum
Head Height:	0.088 Inches Nominal
Nut Style:	Blind Rivet W/smooth Round Shank
Nut Diameter:	0.486 Inches Minimum And 0.490 Inches Maximum
Nut Length:	1.360 Inches Minimum And 1.390 Inches Maximum
Err Default:	+0.115/+0.200 Inches
Unable To Decode:	+0.115 To 0.200 Inches
Shank End Type:	Closed
Thread Series:	Unf
Thread Quantity Per Inch:	24
Nominal Thread Size:	0.375 Inches
Material:	Aluminum Alloy Overall
Material Document And Classification:	Mil-r-1150 Mil Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625,ty 2 Mil Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1329 Professional/industrial Association Standard

How to Order

Order this rivnut from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1329A6B200> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.