

Description

Thread Size: 3/8", Nut Length: 1-25/64"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|-------------------|
| SKU / Model: | NAS1329A6B200 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5310-00-151-5434 |
| Schedule B: | 7616.10.1000 |
| ECCN: | 9A991 |
| National Motor Freight: | 013540, Alum Nuts |

NO IMAGE
AVAILABLE

P/N NAS1329A6B200 Specifications

| | |
|---|--|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Head Style: | Flat |
| Head Diameter: | 0.766 Inches Minimum And 0.796 Inches Maximum |
| Head Height: | 0.088 Inches Nominal |
| Nut Style: | Blind Rivet W/smooth Round Shank |
| Nut Diameter: | 0.486 Inches Minimum And 0.490 Inches Maximum |
| Nut Length: | 1.360 Inches Minimum And 1.390 Inches Maximum |
| Err Default: | +0.115/+0.200 Inches |
| Unable To Decode: | +0.115 To 0.200 Inches |
| Shank End Type: | Closed |
| Thread Series: | Unf |
| Thread Quantity Per Inch: | 24 |
| Nominal Thread Size: | 0.375 Inches |
| Material: | Aluminum Alloy Overall |
| Material Document And Classification: | Mil-r-1150 Mil Spec Single Material Response Overall |
| Surface Treatment: | Anodize Overall |
| Surface Treatment Document And Classification: | Mil-a-8625,ty 2 Mil Spec Single Treatment Response Overall |
| Specification/standard Data: | 80205-nas1329 Professional/Industrial Association Standard |

How to Order

Order this rivnut from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1329A6B200> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.