

## P/N NAS1329C04K60

### **Description**

Thread: 4-40, Thread Size: 7/64", Nut Length: 23/64

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS1329C04K60

Minimum Qty (MOQ): 10

NSN: 5310-01-119-4367

Schedule B: 7318.16.0085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1329C04K60 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Head Style:	Flat Keyed
Head Diameter:	0.255 Inches Minimum And 0.285 Inches Maximum
Key Length:	0.023 Inches Maximum
Head Height:	0.025 Inches Nominal
Nut Style:	Blind Rivet W/smooth Round Shank
Nut Diameter:	0.151 Inches Minimum And 0.155 Inches Maximum
Nut Length:	0.330 Inches Minimum And 0.360 Inches Maximum
Err Default:	+0.010/+0.060 Inches
Shank End Type:	Open
Thread Series:	Unc
Thread Quantity Per Inch:	40
Nominal Thread Size:	0.112 Inches
Material:	Steel Comp 430 Overall
Material Document And Classification:	66 Fed Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall

## **How to Order**

Order this plain blind rivet nut from our inventory online by visiting <a href="https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1329C04K60">https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1329C04K60</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1329C04K60">https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1329C04K60</a> and selecting the