

P/N NAS1329C3KB180

Description

Thread Size: 3/16", Nut Length: 29/32", flat keyed head, rivnut, NAS1329 series nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS1329C3KB180

Minimum Qty (MOQ): 20

NSN: 5310-00-999-4025

Schedule B: 7318.16.0085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)







^{*} See page 2 for technical characteristics

P/N NAS1329C3KB180 Specifications

| Thread Class: | 3b |
|--|--|
| Thread Direction: | Right-hand |
| Head Style: | Flat Keyed |
| Head Diameter: | 0.391 Inches Minimum And 0.421 Inches Maximum |
| Key Length: | 0.061 Inches Nominal |
| Head Height: | 0.038 Inches Nominal |
| Nut Style: | Blind Rivet W/smooth Round Shank |
| Nut Diameter: | 0.246 Inches Minimum And 0.250 Inches Maximum |
| Nut Length: | 0.876 Inches Minimum And 0.906 Inches Maximum |
| Err Default: | +0.130/+0.180 Inches |
| Shank End Type: | Closed |
| Thread Series: | Unf |
| Thread Quantity Per Inch: | 32 |
| Nominal Thread Size: | 0.190 Inches |
| Material: | Steel Comp 430 Overall |
| Material Document And Classification: | Qq-w-423,form 1 Fed Spec Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35,ty 2 Fed Spec Single Treatment Response Overall |
| Specification/standard Data: | 80205-nas1329 Professional/industrial Association Standard |

How to Order

Order this plain blind rivet nut from our inventory online by visiting https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1329C3KB180 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.