

**Description**

Thread Size: 3/16", Nut Length: 29/32", flat keyed head, rivnut, NAS1329 series nut

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS1329C3KB180                            |
| Minimum Qty (MOQ):      | 20  |
| NSN:                    | 5310-00-999-4025                          |
| Schedule B:             | 7318.16.0085                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



\* See page 2 for technical characteristics

## P/N NAS1329C3KB180 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3b   |
| <b>Thread Direction:</b>                              | Right-hand   |
| <b>Head Style:</b>                                    | Flat Keyed   |
| <b>Head Diameter:</b>                                 | 0.391 Inches Minimum And 0.421 Inches Maximum              |
| <b>Key Length:</b>                                    | 0.061 Inches Nominal                                       |
| <b>Head Height:</b>                                   | 0.038 Inches Nominal                                       |
| <b>Nut Style:</b>                                     | Blind Rivet W/smooth Round Shank                           |
| <b>Nut Diameter:</b>                                  | 0.246 Inches Minimum And 0.250 Inches Maximum              |
| <b>Nut Length:</b>                                    | 0.876 Inches Minimum And 0.906 Inches Maximum              |
| <b>Err Default:</b>                                   | +0.130/+0.180 Inches                                       |
| <b>Shank End Type:</b>                                | Closed   |
| <b>Thread Series:</b>                                 | Unf  |
| <b>Thread Quantity Per Inch:</b>                      | 32   |
| <b>Nominal Thread Size:</b>                           | 0.190 Inches   |
| <b>Material:</b>                                      | Steel Comp 430 Overall                                     |
| <b>Material Document And Classification:</b>          | Qq-w-423,form 1 Fed Spec Single Material Response Overall  |
| <b>Surface Treatment:</b>                             | Passivate Overall  |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-35,ty 2 Fed Spec Single Treatment Response Overall    |
| <b>Specification/standard Data:</b>                   | 80205-nas1329 Professional/industrial Association Standard |

## How to Order

Order this plain blind rivet nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1329C3KB180> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.