

# P/N NAS1329C4K200

Military-Fasteners.com

#### Description

Thread Size: 1/4", Nut Length: 3/4

\* Manufacturer certifications are shipped with your order  $\underline{\mathsf{FREE}}$  of charge

#### Order this part online

#### **Additional Information**

SKU / Model:	NAS1329C4K200
Minimum Qty (MOQ):	5
NSN:	5310-00-455-9966
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N NAS1329C4K200 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Head Style:	Flat Keyed
Head Diameter:	0.460 Inches Minimum And 0.490 Inches Maximum
Key Length:	0.093 Inches Nominal
Head Height:	0.058 Inches Nominal
Nut Style:	Blind Rivet W/smooth Round Shank
Nut Diameter:	0.328 Inches Minimum And 0.332 Inches Maximum
Nut Length:	0.735 Inches Minimum And 0.765 Inches Maximum
Err Default:	+0.140/+0.200 Inches
Unable To Decode:	+0.140 To 0.200 Inches
Shank End Type:	Open
Thread Series:	Unf
Thread Quantity Per Inch:	28
Nominal Thread Size:	0.250 Inches
Material:	Steel Comp 430 Overall
Material Document And Classification:	Qq-w-423,form 1 Fed Spec Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Mil-s-5002 Mil Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1329 Professional/industrial Association Standard

### How to Order

Order this rivnut from our inventory online by visiting <u>https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1329C4K200</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out<u>here</u> to complete your order.