

# P/N NAS1329C4K260

### **Description**

Thread Size: 1/4", Nut Length: 13/16", flat head, fine thread, NAS1329 series nut

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS1329C4K260

Minimum Qty (MOQ): 5

NSN: 5310-01-435-9671

Schedule B: 7318.16.0085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)







<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1329C4K260 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Head Style:	Flat
Head Diameter:	0.400 Inches Minimum And 0.490 Inches Maximum
Head Height:	0.058 Inches Nominal
Nut Style:	Blind Rivet W/smooth Round Shank
Nut Diameter:	0.328 Inches Minimum And 0.332 Inches Maximum
Nut Length:	0.797 Inches Minimum And 0.827 Inches Maximum
Err Default:	+0.200/+0.260 Inches
Shank End Type:	Open
Thread Series:	Unf
Thread Quantity Per Inch:	28
Nominal Thread Size:	0.250 Inches
Material:	Steel Comp 430 Overall
Material Document And Classification:	Astm A276 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Type 2 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1329 Professional/industrial Association Standard

## **How to Order**

Order this plain blind rivet nut from our inventory online by visiting <a href="https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1329C4K260">https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1329C4K260</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1329C4K260">https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1329C4K260</a> and selecting the