

Description

Thread Size: 1/4", Nut Length: 1-1/16", NAS1329 series nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS1329C4KB200 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5310-00-999-4029 |
| Schedule B: | 7318.15.2010 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N NAS1329C4KB200 Specifications

| | |
|---|--|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Head Style: | Flat Keyed |
| Head Diameter: | 0.460 Inches Minimum And 0.490 Inches Maximum |
| Key Length: | 0.093 Inches Nominal |
| Head Height: | 0.058 Inches Nominal |
| Nut Style: | Blind Rivet W/smooth Round Shank |
| Nut Diameter: | 0.328 Inches Minimum And 0.332 Inches Maximum |
| Nut Length: | 1.047 Inches Minimum And 1.077 Inches Maximum |
| Err Default: | +0.140/+0.200 Inches |
| Shank End Type: | Closed |
| Thread Series: | Unf |
| Thread Quantity Per Inch: | 28 |
| Nominal Thread Size: | 0.250 Inches |
| Material: | Steel Comp 430 Overall |
| Material Document And Classification: | Qq-w-423,form 1 Fed Spec Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35,ty 2 Fed Spec Single Treatment Response Overall |
| Specification/standard Data: | 80205-nas1329 Professional/industrial Association Standard |

How to Order

Order this plain blind rivet nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1329C4KB200> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.