

**Description**

Thread Size: 3/8", Nut Length: 1-25/64

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1329C6K200
Minimum Qty (MOQ):	5
NSN:	5310-01-321-1053
Schedule B:	7318.16.0085
ECCN:	EAR99

NO IMAGE  
AVAILABLE

## P/N NAS1329C6K200 Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Head Style:</b>	Flat Keyed
<b>Head Diameter:</b>	0.766 Inches Minimum And 0.796 Inches Maximum
<b>Key Length:</b>	0.128 Inches Nominal
<b>Head Height:</b>	0.088 Inches Nominal
<b>Nut Style:</b>	Blind Rivet W/smooth Round Shank
<b>Nut Diameter:</b>	0.486 Inches Minimum And 0.490 Inches Maximum
<b>Nut Length:</b>	1.360 Inches Minimum And 1.390 Inches Maximum
<b>Err Default:</b>	+0.115/+0.200 Inches
<b>Shank End Type:</b>	Open
<b>Thread Series:</b>	Unf
<b>Thread Quantity Per Inch:</b>	24
<b>Nominal Thread Size:</b>	0.375 Inches
<b>Material:</b>	Steel Comp 430 Overall
<b>Material Document And Classification:</b>	Qq-w-423,form 1 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35,ty 2 Fed Spec Single Treatment Response Overall
<b>Specification/standard Data:</b>	80205-nas1329 Professional/industrial Association Standard

## How to Order

Order this plain blind rivet nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1329C6K200> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.