

Description

Thread Size: 3/8", Nut Length: 1-25/64

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1329C6K200
Minimum Qty (MOQ):	5
NSN:	5310-01-321-1053
Schedule B:	7318.16.0085
ECCN:	EAR99

NO IMAGE
AVAILABLE

P/N NAS1329C6K200 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Head Style:	Flat Keyed
Head Diameter:	0.766 Inches Minimum And 0.796 Inches Maximum
Key Length:	0.128 Inches Nominal
Head Height:	0.088 Inches Nominal
Nut Style:	Blind Rivet W/smooth Round Shank
Nut Diameter:	0.486 Inches Minimum And 0.490 Inches Maximum
Nut Length:	1.360 Inches Minimum And 1.390 Inches Maximum
Err Default:	+0.115/+0.200 Inches
Shank End Type:	Open
Thread Series:	Unf
Thread Quantity Per Inch:	24
Nominal Thread Size:	0.375 Inches
Material:	Steel Comp 430 Overall
Material Document And Classification:	Qq-w-423,form 1 Fed Spec Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35,ty 2 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1329 Professional/industrial Association Standard

How to Order

Order this plain blind rivet nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1329C6K200> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.