

Description

Thread Size: 1/8", Nut Length: 29/64"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | NAS1329H06K75L |
| Minimum Qty (MOQ): | 15 EA |
| NSN: | 5310-01-070-2997 |
| Schedule B: | 7318.16.0085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N NAS1329H06K75L Specifications

| | |
|---|--|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Head Style: | Flat Keyed |
| Head Diameter: | 0.310 Inches Minimum And 0.340 Inches Maximum |
| Key Length: | 0.023 Inches Maximum |
| Head Height: | 0.032 Inches Nominal |
| Locking Feature: | Prevailing Torque All Metal Design |
| Nut Style: | Blind Rivet W/smooth Round Shank |
| Nut Diameter: | 0.185 Inches Minimum And 0.189 Inches Maximum |
| Nut Length: | 0.423 Inches Minimum And 0.453 Inches Maximum |
| Nut Grip Range: | +0.010/+0.075 Inches |
| Shank End Type: | Open |
| Thread Series: | Unc |
| Thread Quantity Per Inch: | 32 |
| Nominal Thread Size: | 0.138 Inches |
| Material: | Steel Comp 4037 Overall |
| Material Document And Classification: | Astm A547 Assn Std Single Material Response Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall |
| Specification/standard Data: | 80205-nas1329 Professional/Industrial Association Standard |

How to Order

Order this rivnut from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1329H06K75L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.