

## P/N NAS1329H08K75

## **Description**

Blind rivet with smooth round shank. Thread: 8-32

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

### **Additional Information**

#### **Alternate Part Numbers**

#### AECH8K75

SKU / Model: NAS1329H08K75

Minimum Qty (MOQ): 20

NSN: 5310-01-399-6977

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









# P/N NAS1329H08K75 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Head Style:	Flat Keyed
Head Diameter:	0.342 Inches Minimum And 0.372 Inches Maximum
Key Length:	0.055 Inches Maximum
Head Height:	0.032 Inches Nominal
Nut Style:	Blind Rivet W/smooth Round Shank
Nut Diameter:	0.217 Inches Minimum And 0.221 Inches Maximum
Nut Length:	0.423 Inches Minimum And 0.453 Inches Maximum
Err Default:	+0.010/+0.075 Inches
Shank End Type:	Open
Thread Series:	Unc
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.164 Inches
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Specification/standard Data:	80205-nas1329 Professional/industrial Association Standard

## **How to Order**

Order this plain blind rivet nut from our inventory online by visiting <a href="https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1329H08K75">https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1329H08K75</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1329H08K75">https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1329H08K75</a> and selecting the