

Description

Thread Size: 3/16", Nut Length: 3/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1329H3K280L
Minimum Qty (MOQ):	15 EA
NSN:	5310-01-072-4717
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1329H3K280L Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Head Style:	Flat Keyed
Head Diameter:	0.391 Inches Minimum And 0.421 Inches Maximum
Key Length:	0.023 Inches Maximum
Head Height:	0.038 Inches Nominal
Locking Feature:	Prevailing Torque All Metal Design
Nut Style:	Blind Rivet W/smooth Round Shank
Nut Diameter:	0.246 Inches Minimum And 0.250 Inches Maximum
Nut Length:	0.735 Inches Minimum And 0.765 Inches Maximum
Nut Grip Range:	+0.230/+0.280 Inches
Shank End Type:	Open
Thread Series:	Unf
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.190 Inches
Material:	Steel Comp 4037 Overall
Material Document And Classification:	Astm A547 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1329 Professional/industrial Association Standard

How to Order

Order this rivnut from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1329H3K280L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.