

Description

Thread Size: 1/4", Nut Length: 3/4

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[RCH2528K200LCY](#) [AECH2528K200L](#)

SKU / Model:	NAS1329H4K200L
Minimum Qty (MOQ):	10
NSN:	5310-01-082-7083
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS1329H4K200L Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Head Style:	Flat Keyed
Head Diameter:	0.460 Inches Minimum And 0.490 Inches Maximum
Key Length:	0.035 Inches Maximum
Head Height:	0.058 Inches Nominal
Locking Feature:	Prevailing Torque All Metal Design
Nut Style:	Blind Rivet W/smooth Round Shank
Nut Diameter:	0.328 Inches Minimum And 0.332 Inches Maximum
Nut Length:	0.735 Inches Minimum And 0.765 Inches Maximum
Nut Grip Range:	+0.140/+0.200 Inches
Shank End Type:	Open
Thread Series:	Unf
Thread Quantity Per Inch:	28
Nominal Thread Size:	0.250 Inches
Material:	Steel Comp 4037 Overall
Material Document And Classification:	Astm A547 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 2 Fed Spec All Treatment Responses Overall
Specification/standard Data:	80205-nas1329 Professional/industrial Association Standard

How to Order

Order this plain blind rivet nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1329H4K200L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.