

## P/N NAS1329S04K60

## **Description**

Thread Size: 7/64", Nut Length: 11/32"

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS1329S04K60

Minimum Qty (MOQ): 20 EA

NSN: 5310-00-113-6235

Schedule B: 7318.16.0085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1329S04K60 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Head Style:	Flat Keyed
Head Diameter:	0.270 Inches Nominal
Key Length:	0.048 Inches Nominal
Head Height:	0.025 Inches Nominal
Nut Style:	Blind Rivet W/smooth Round Shank
Nut Diameter:	0.151 Inches Minimum And 0.155 Inches Maximum
Nut Length:	0.345 Inches Nominal
Err Default:	+0.010/+0.060 Inches
Unable To Decode:	+0.010 To 0.060 Inches
Shank End Type:	Open
Thread Series:	Unc
Thread Quantity Per Inch:	40
Nominal Thread Size:	0.112 Inches
Material:	Steel Comp 1108 Overall Or Steel Comp 1110 Overall
Material Document And Classification:	Aisi Assn Std All Material Responses Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall

### **How to Order**

Order this rivnut from our inventory online by visiting <a href="https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1329S04K60">https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1329S04K60</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.