

Description

Thread Size: 1/8", Nut Length: 1/2"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS1329S06K120                            |
| Minimum Qty (MOQ):      | 95 EA                                     |
| NSN:                    | 5310-01-073-2539                          |
| Schedule B:             | 7318.16.0085                              |
| ECCN:                   | 9A991                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



\* See page 2 for technical characteristics

## P/N NAS1329S06K120 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3b   |
| <b>Thread Direction:</b>                              | Right-hand   |
| <b>Head Style:</b>                                    | Flat Keyed   |
| <b>Head Diameter:</b>                                 | 0.310 Inches Minimum And 0.340 Inches Maximum                      |
| <b>Key Length:</b>                                    | 0.023 Inches Maximum   |
| <b>Head Height:</b>                                   | 0.032 Inches Nominal   |
| <b>Nut Style:</b>                                     | Blind Rivet W/smooth Round Shank                                   |
| <b>Nut Diameter:</b>                                  | 0.185 Inches Minimum And 0.189 Inches Maximum                      |
| <b>Nut Length:</b>                                    | 0.485 Inches Minimum And 0.515 Inches Maximum                      |
| <b>Err Default:</b>                                   | +0.075/+0.120 Inches   |
| <b>Shank End Type:</b>                                | Open   |
| <b>Thread Series:</b>                                 | Unc  |
| <b>Thread Quantity Per Inch:</b>                      | 32   |
| <b>Nominal Thread Size:</b>                           | 0.138 Inches   |
| <b>Material:</b>                                      | Steel Comp 1108 Overall Or Steel Comp 1110 Overall                 |
| <b>Material Document And Classification:</b>          | Astm A549 Assn Std All Material Responses Overall                  |
| <b>Surface Treatment:</b>                             | Cadmium Overall And Chromate Overall                               |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416,type 2 Class 2 Fed Spec Single Treatment Response Overall |
| <b>Specification/standard Data:</b>                   | 80205-nas1329 Professional/industrial Association Standard         |

## How to Order

Order this rivnut from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1329S06K120> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.