

Description

Thread Size: 5/32", Nut Length: 5/8

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1329S08B75
Minimum Qty (MOQ):	50
NSN:	5310-00-943-5324
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS1329S08B75 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Head Style:	Flat
Head Diameter:	0.342 Inches Minimum And 0.372 Inches Maximum
Head Height:	0.032 Inches Nominal
Nut Style:	Blind Rivet W/smooth Round Shank
Nut Diameter:	0.217 Inches Minimum And 0.221 Inches Maximum
Nut Length:	0.610 Inches Minimum And 0.640 Inches Maximum
Err Default:	+0.010/+0.075 Inches
Shank End Type:	Closed
Thread Series:	Unc
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.164 Inches
Material:	Steel Comp 1109 Overall Or Steel Comp 1108 Overall
Material Document And Classification:	Sae Assn Std All Material Responses Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1329 Professional/industrial Association Standard

How to Order

Order this plain blind rivet nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1329S08B75> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.