

**Description**

Thread Size: 1/4", Nut Length: 5/8", rivnut

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1329S3130
Minimum Qty (MOQ):	50
NSN:	5310-00-269-3466
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N NAS1329S3-130 Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Head Style:</b>	Flat
<b>Head Diameter:</b>	0.391 Inches Minimum And 0.421 Inches Maximum
<b>Head Height:</b>	0.038 Inches Nominal
<b>Nut Style:</b>	Blind Rivet W/smooth Round Shank
<b>Nut Diameter:</b>	0.246 Inches Minimum And 0.250 Inches Maximum
<b>Nut Length:</b>	0.579 Inches Minimum And 0.609 Inches Maximum
<b>Err Default:</b>	+0.080/+0.130 Inches
<b>Unable To Decode:</b>	+0.080 To 0.130 Inches
<b>Shank End Type:</b>	Open
<b>Thread Series:</b>	Unf
<b>Thread Quantity Per Inch:</b>	32
<b>Nominal Thread Size:</b>	0.190 Inches
<b>Material:</b>	Steel Comp 1108 Overall Or Steel Comp 1110 Overall
<b>Material Document And Classification:</b>	Fed Std 66,aisi 1108 Fed Std 1st Material Response Overall Or Fed Std 66,aisi 1110 Fed Std 2nd Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall

## How to Order

Order this plain blind rivet nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1329S3-130> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.