

P/N NAS1329S3-80

Description

Thread Size: 1/4", Nut Length: 1/2", rivnut, flat head, open shank, alternate to MS27130S25, NAS1329 series nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS1329S380

Minimum Qty (MOQ): 50

NSN: 5310-00-945-0499

Schedule B: 7318.16.0085

ECCN: EAR99

National Motor Freight: 077140, Fruits Dried / Evaporated Noi









P/N NAS1329S3-80 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Head Style:	Flat
Head Diameter:	0.391 Inches Minimum And 0.421 Inches Maximum
Head Height:	0.038 Inches Nominal
Nut Style:	Blind Rivet W/smooth Round Shank
Nut Diameter:	0.246 Inches Minimum And 0.250 Inches Maximum
Nut Length:	0.516 Inches Minimum And 0.546 Inches Maximum
Err Default:	+0.010/+0.080 Inches
Shank End Type:	Open
Thread Series:	Unf
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.190 Inches
Material:	Steel Comp 4037 Overall
Material Document And Classification:	Qq-w-405 Fed Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1329 Professional/industrial Association Standard

How to Order

Order this blind rivet plain nut from our inventory online by visiting https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1329S3-80 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1329S3-80 and selecting the