

Description

Thread Size: 3/16", Nut Length: 39/64", Rivnut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[AES10-K-130CSI](#) [S10K130](#) [MS27130-S26K](#)

| | |
|-------------------------|---|
| SKU / Model: | NAS1329S3K130 |
| Minimum Qty (MOQ): | 50 |
| NSN: | 5310-01-186-3484 |
| Schedule B: | 7318.16.0085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N NAS1329S3K130 Specifications

| | |
|---|---|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Head Style: | Flat Keyed |
| Head Diameter: | 0.391 Inches Minimum And 0.421 Inches Maximum |
| Key Length: | 0.023 Inches Maximum |
| Head Height: | 0.038 Inches Nominal |
| Nut Style: | Blind Rivet W/smooth Round Shank |
| Nut Diameter: | 0.246 Inches Minimum And 0.250 Inches Maximum |
| Nut Length: | 0.579 Inches Minimum And 0.609 Inches Maximum |
| Err Default: | +0.080/+0.130 Inches |
| Shank End Type: | Open |
| Thread Series: | Unf |
| Thread Quantity Per Inch: | 32 |
| Nominal Thread Size: | 0.190 Inches |
| Material: | Steel Comp 1108 Overall Or Steel Comp 1110 Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall |
| Specification/standard Data: | 80205-nas1329 Professional/industrial Association Standard |

How to Order

Order this plain blind rivet nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1329S3K130> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.