

## P/N NAS1329S3KB130

## **Description**

Thread Size: 3/16", Nut Length: 53/64"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS1329S3KB130

Minimum Qty (MOQ): 30 EA

NSN: 5310-00-999-4188

Schedule B: 7616.10.9090

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1329S3KB130 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Head Style:	Flat Keyed
Head Diameter:	0.391 Inches Minimum And 0.421 Inches Maximum
Key Length:	0.061 Inches Nominal
Head Height:	0.038 Inches Nominal
Nut Style:	Blind Rivet W/smooth Round Shank
Nut Diameter:	0.246 Inches Minimum And 0.250 Inches Maximum
Nut Length:	0.828 Inches Minimum And 0.858 Inches Maximum
Err Default:	+0.080/+0.130 Inches
Shank End Type:	Closed
Thread Series:	Unf
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.190 Inches
Material:	Steel Comp 1108 Overall Or Steel Comp 1110 Overall
Material Document And Classification:	Qq-w-405 Fed Spec All Material Responses Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1329 Professional/industrial Association Standard

### **How to Order**

Order this rivnut from our inventory online by visiting <a href="https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1329S3KB130">https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1329S3KB130</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.