

Description

Thread Size: 1/4", Nut Length: 11/16

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[AES2528K140CSI](#) [MS27130-S38K](#)

SKU / Model:	NAS1329S4K140
Minimum Qty (MOQ):	50
NSN:	5310-00-063-2518
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	077140, Fruits Dried / Evaporated Noi



* See page 2 for technical characteristics

P/N NAS1329S4K140 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Head Style:	Flat Keyed
Head Diameter:	0.460 Inches Minimum And 0.490 Inches Maximum
Key Length:	0.098 Inches Nominal
Head Height:	0.058 Inches Nominal
Nut Style:	Blind Rivet W/smooth Round Shank
Nut Diameter:	0.328 Inches Minimum And 0.332 Inches Maximum
Nut Length:	0.672 Inches Minimum And 0.702 Inches Maximum
Err Default:	+0.080/+0.140 Inches
Unable To Decode:	+0.080 To 0.140 Inches
Shank End Type:	Open
Thread Series:	Unf
Thread Quantity Per Inch:	28
Nominal Thread Size:	0.250 Inches
Material:	Steel Comp 1109 Overall
Material Document And Classification:	66 Fed Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1329 Professional/industrial Association Standard

How to Order

Order this plain blind rivet nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1329S4K140> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.