

Description

Thread Size: 1/4", Nut Length: 11/16

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[AES2528K140CSI](#) [MS27130-S38K](#)

| | |
|-------------------------|---------------------------------------|
| SKU / Model: | NAS1329S4K140 |
| Minimum Qty (MOQ): | 50 |
| NSN: | 5310-00-063-2518 |
| Schedule B: | 7318.16.0085 |
| ECCN: | EAR99 |
| National Motor Freight: | 077140, Fruits Dried / Evaporated Noi |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1329S4K140 Specifications

| | |
|---|---|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Head Style: | Flat Keyed |
| Head Diameter: | 0.460 Inches Minimum And 0.490 Inches Maximum |
| Key Length: | 0.098 Inches Nominal |
| Head Height: | 0.058 Inches Nominal |
| Nut Style: | Blind Rivet W/smooth Round Shank |
| Nut Diameter: | 0.328 Inches Minimum And 0.332 Inches Maximum |
| Nut Length: | 0.672 Inches Minimum And 0.702 Inches Maximum |
| Err Default: | +0.080/+0.140 Inches |
| Unable To Decode: | +0.080 To 0.140 Inches |
| Shank End Type: | Open |
| Thread Series: | Unf |
| Thread Quantity Per Inch: | 28 |
| Nominal Thread Size: | 0.250 Inches |
| Material: | Steel Comp 1109 Overall |
| Material Document And Classification: | 66 Fed Std Single Material Response Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall |
| Specification/standard Data: | 80205-nas1329 Professional/Industrial Association Standard |

How to Order

Order this plain blind rivet nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1329S4K140> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.