

**Description**

Thread Size: 1/4", Nut Length: 11/16

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[AES2528K140CSI](#) [MS27130-S38K](#)

SKU / Model:	NAS1329S4K140
Minimum Qty (MOQ):	50
NSN:	5310-00-063-2518
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	077140, Fruits Dried / Evaporated Noi

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS1329S4K140 Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Head Style:</b>	Flat Keyed
<b>Head Diameter:</b>	0.460 Inches Minimum And 0.490 Inches Maximum
<b>Key Length:</b>	0.098 Inches Nominal
<b>Head Height:</b>	0.058 Inches Nominal
<b>Nut Style:</b>	Blind Rivet W/smooth Round Shank
<b>Nut Diameter:</b>	0.328 Inches Minimum And 0.332 Inches Maximum
<b>Nut Length:</b>	0.672 Inches Minimum And 0.702 Inches Maximum
<b>Err Default:</b>	+0.080/+0.140 Inches
<b>Unable To Decode:</b>	+0.080 To 0.140 Inches
<b>Shank End Type:</b>	Open
<b>Thread Series:</b>	Unf
<b>Thread Quantity Per Inch:</b>	28
<b>Nominal Thread Size:</b>	0.250 Inches
<b>Material:</b>	Steel Comp 1109 Overall
<b>Material Document And Classification:</b>	66 Fed Std Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
<b>Specification/standard Data:</b>	80205-nas1329 Professional/Industrial Association Standard

## How to Order

Order this plain blind rivet nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1329S4K140> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.