

Description

Thread Size: 1/4", Nut Length: 15/16"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1329S4KB80
Minimum Qty (MOQ):	5 EA
NSN:	5310-01-399-3130
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS1329S4KB80 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Head Style:	Flat Keyed
Head Diameter:	0.460 Inches Minimum And 0.490 Inches Maximum
Key Length:	0.062 Inches Nominal
Nut Style:	Blind Rivet W/smooth Round Shank
Nut Diameter:	0.328 Inches Minimum And 0.332 Inches Maximum
Nut Length:	0.922 Inches Minimum And 0.952 Inches Maximum
Err Default:	+0.020/+0.080 Inches
Shank End Type:	Closed
Thread Series:	Unf
Thread Quantity Per Inch:	28
Nominal Thread Size:	0.250 Inches
Material:	Steel Comp 1108 Overall Or Steel Comp 1110 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty2cl2 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1329 Professional/industrial Association Standard

How to Order

Order this rivnut from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1329S4KB80> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.