

P/N NAS1330A04K81

Description

Thread Size: 7/64", Nut Length: 3/8

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS1330A04K81

Minimum Qty (MOQ): 25

NSN: 5310-00-538-7149

Schedule B: 7616.10.1000

ECCN: EAR99

National Motor Freight: 013540, Alum Nuts









^{*} See page 2 for technical characteristics

P/N NAS1330A04K81 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Head Style:	Flat Countersunk Reverse Keyed
Head Diameter:	0.263 Inches Nominal
Key Length:	0.051 Inches Maximum
Head Height:	0.051 Inches Maximum
Nut Style:	Blind Rivet W/smooth Round Shank
Nut Diameter:	0.151 Inches Minimum And 0.155 Inches Maximum
Nut Length:	0.355 Inches Minimum And 0.385 Inches Maximum
Err Default:	+0.050/+0.081 Inches
Unable To Decode:	+0.050 To 0.081 Inches
Shank End Type:	Open
Thread Series:	Unc
Thread Quantity Per Inch:	40
Nominal Thread Size:	0.112 Inches
Head Countersink Angle:	99.00 Degrees Minimum And 101.00 Degrees Maximum
Material:	Aluminum Alloy Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625,ty 2 Mil Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1330 Professional/industrial Association Standard

How to Order

Order this self-locking extended washer nut from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+extended+washer+nuts/NAS1330A04K81 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.