

**Description**

Thread Size: 7/64", Nut Length: 3/8

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |                   |
|-------------------------|-------------------|
| SKU / Model:            | NAS1330A04K81     |
| Minimum Qty (MOQ):      | 25                |
| NSN:                    | 5310-00-538-7149  |
| Schedule B:             | 7616.10.1000      |
| ECCN:                   | EAR99             |
| National Motor Freight: | 013540, Alum Nuts |



## P/N NAS1330A04K81 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3b   |
| <b>Thread Direction:</b>                              | Right-hand   |
| <b>Head Style:</b>                                    | Flat Countersunk Reverse Keyed                             |
| <b>Head Diameter:</b>                                 | 0.263 Inches Nominal                                       |
| <b>Key Length:</b>                                    | 0.051 Inches Maximum                                       |
| <b>Head Height:</b>                                   | 0.051 Inches Maximum                                       |
| <b>Nut Style:</b>                                     | Blind Rivet W/smooth Round Shank                           |
| <b>Nut Diameter:</b>                                  | 0.151 Inches Minimum And 0.155 Inches Maximum              |
| <b>Nut Length:</b>                                    | 0.355 Inches Minimum And 0.385 Inches Maximum              |
| <b>Err Default:</b>                                   | +0.050/+0.081 Inches                                       |
| <b>Unable To Decode:</b>                              | +0.050 To 0.081 Inches                                     |
| <b>Shank End Type:</b>                                | Open   |
| <b>Thread Series:</b>                                 | Unc  |
| <b>Thread Quantity Per Inch:</b>                      | 40   |
| <b>Nominal Thread Size:</b>                           | 0.112 Inches   |
| <b>Head Countersink Angle:</b>                        | 99.00 Degrees Minimum And 101.00 Degrees Maximum           |
| <b>Material:</b>                                      | Aluminum Alloy Overall                                     |
| <b>Surface Treatment:</b>                             | Anodize Overall  |
| <b>Surface Treatment Document And Classification:</b> | Mil-a-8625,ty 2 Mil Spec Single Treatment Response Overall |
| <b>Specification/standard Data:</b>                   | 80205-nas1330 Professional/industrial Association Standard |

## How to Order

Order this self-locking extended washer nut from our inventory online by visiting [https://military-fasteners.com/nuts/self\\_locking+extended+washer+nuts/NAS1330A04K81](https://military-fasteners.com/nuts/self_locking+extended+washer+nuts/NAS1330A04K81) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.