

Description

Thread Size: 1/8", Nut Length: 1/2

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1330A06161
Minimum Qty (MOQ):	25
NSN:	5310-01-244-4514
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013540, Alum Nuts



* See page 2 for technical characteristics

P/N NAS1330A06-161 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Head Style:	Flat Countersunk
Head Diameter:	0.323 Inches Nominal
Nut Style:	Blind Rivet W/smooth Round Shank
Nut Diameter:	0.185 Inches Minimum And 0.189 Inches Maximum
Nut Length:	0.485 Inches Minimum And 0.515 Inches Maximum
Err Default:	+0.106/+0.161 Inches
Shank End Type:	Open
Thread Series:	Unc
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.1380 Inches
Head Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Aluminum Alloy 5056 Overall Or Aluminum Alloy 6053 Overall
Material Document And Classification:	Qq-a-430 Fed Spec All Material Responses Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-h-8625 Ty 2 Mil Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1330 Professional/industrial Association Standard

How to Order

Order this plain blind rivet nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1330A06-161> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.