

# P/N NAS1330A06K161

## **Description**

Thread: 6-32, Thread Size: 1/8", Nut Length: 1/2",

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

### **Additional Information**

#### **Alternate Part Numbers**

## AEA6K161 MS27130-A88K

SKU / Model: NAS1330A06K161

Minimum Qty (MOQ): 25

NSN: 5310-00-255-1454

Schedule B: 7616.10.3000

ECCN: EAR99

National Motor Freight: 013540, Alum Nuts







<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1330A06K161 Specifications

Thread Class:	2b
Thread Direction:	Right-hand
Head Style:	Flat Countersunk Reverse Keyed
Head Diameter:	0.323 Inches Nominal
Key Length:	0.063 Inches Nominal
Head Height:	0.063 Inches Nominal
Nut Style:	Blind Rivet W/smooth Round Shank
Nut Diameter:	0.189 Inches Nominal
Nut Length:	0.500 Inches Nominal
Err Default:	+0.106/+0.161 Inches
Unable To Decode:	+0.106 To 0.161 Inches
Shank End Type:	Open
Thread Series:	Unc
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.138 Inches
Head Countersink Angle:	100.0 Degrees Nominal
Material:	Aluminum Alloy Overall
Material Document And Classification:	6053 Fscm 97282 Mfr Ref Single Material Response Overall
Surface Treatment:	Anodize Overall
Specification/standard Data:	80205-nas1330 Professional/industrial Association Standard

## **How to Order**

Order this plain blind rivet nut from our inventory online by visiting <a href="https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1330A06K161">https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1330A06K161</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.