

**Description**

Thread Size: 1/8", Nut Length: 5/8", Rivnut

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1330A06K241
Minimum Qty (MOQ):	25
NSN:	5310-00-194-8033
Schedule B:	7616.10.1000
ECCN:	EAR99
National Motor Freight:	013540, Alum Nuts



\* See page 2 for technical characteristics

## P/N NAS1330A06K241 Specifications

<b>Thread Class:</b>	2b
<b>Thread Direction:</b>	Right-hand
<b>Head Style:</b>	Flat Countersunk Reverse Keyed
<b>Head Diameter:</b>	0.323 Inches Nominal
<b>Key Length:</b>	0.063 Inches Nominal
<b>Head Height:</b>	0.063 Inches Nominal
<b>Nut Style:</b>	Blind Rivet W/smooth Round Shank
<b>Nut Diameter:</b>	0.189 Inches Nominal
<b>Nut Length:</b>	0.625 Inches Nominal
<b>Err Default:</b>	+0.021/+0.041 Inches
<b>Unable To Decode:</b>	+0.021 To 0.041 Inches
<b>Shank End Type:</b>	Open
<b>Thread Series:</b>	Unc
<b>Thread Quantity Per Inch:</b>	32
<b>Nominal Thread Size:</b>	0.138 Inches
<b>Material:</b>	Aluminum Alloy 6053 Overall
<b>Material Document And Classification:</b>	T4 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Anodize Overall

## How to Order

Order this plain blind rivet nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1330A06K241> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.