

P/N NAS1330A08B106

Description

Thread Size: 5/32", Nut Length: 11/16"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	NAS1330A08B106
Minimum Qty (MOQ):	25 EA
NSN:	5310-01-295-3041
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013540, Alum Nuts



^{*} See page 2 for technical characteristics

P/N NAS1330A08B106 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Head Style:	Flat Countersunk
Head Diameter:	0.355 Inches Nominal
Nut Style:	Blind Rivet W/smooth Round Shank
Nut Diameter:	0.217 Inches Minimum And 0.221 Inches Maximum
Nut Length:	0.672 Inches Minimum And 0.702 Inches Maximum
Err Default:	+0.065/+0.106 Inches
Shank End Type:	Closed
Thread Series:	Unc
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.164 Inches
Head Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Aluminum Alloy Overall
Material Document And Classification:	Mil-r-1150 Mil Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625,type 2 Mil Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1330 Professional/industrial Association Standard

How to Order

Order this rivnut from our inventory online by visiting https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1330A08B106 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1330A08B106 and selecting the quantity you