

Description

Thread Size: 5/32", Nut Length: 5/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1330A08K241
Minimum Qty (MOQ):	30 EA
NSN:	5310-00-582-9169
Schedule B:	7616.10.3000
ECCN:	9A991
National Motor Freight:	013540, Alum Nuts

NO IMAGE
AVAILABLE

P/N NAS1330A08K241 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Head Style:	Flat Countersunk Reverse Keyed
Head Diameter:	0.359 Inches Nominal
Key Length:	0.063 Inches Maximum
Head Height:	0.063 Inches Maximum
Nut Style:	Blind Rivet W/smooth Round Shank
Nut Diameter:	0.221 Inches Maximum
Nut Length:	0.625 Inches Nominal
Err Default:	+0.201/+0.241 Inches
Unable To Decode:	+0.201 To 0.241 Inches
Shank End Type:	Open
Thread Series:	Unc
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.164 Inches
Head Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Aluminum Alloy 6053 Overall
Surface Treatment:	Anodize Overall
Specification/standard Data:	80205-nas1330 Professional/industrial Association Standard

How to Order

Order this rivnut from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1330A08K241> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.