

Description

Thread Size: 1/4", Nut Length: 5/8", Rivnut

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[MS27130-A100](#) [AEA10-166](#) [A10-166](#)

SKU / Model:	NAS1330A3166
Minimum Qty (MOQ):	50
NSN:	5310-00-957-6532
Schedule B:	7616.10.1000
ECCN:	EAR99
National Motor Freight:	013540, Alum Nuts



* See page 2 for technical characteristics

P/N NAS1330A3-166 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Head Style:	Flat Countersunk
Head Diameter:	0.391 Inches Nominal
Nut Style:	Blind Rivet W/smooth Round Shank
Nut Diameter:	0.250 Inches Nominal
Nut Length:	0.625 Inches Nominal
Err Default:	+0.116/+0.166 Inches
Shank End Type:	Open
Thread Series:	Unf
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.190 Inches
Head Countersink Angle:	100.00 Degrees Nominal
Material:	Aluminum Alloy 3003 Overall Or Aluminum Alloy 6053 Overall Or Aluminum Alloy 6061 Overall
Material Document And Classification:	Mil-r-1150 Mil Spec All Material Responses Overall
Surface Treatment:	Anodize Overall
Specification/standard Data:	80205-nas1330 Professional/Industrial Association Standard

How to Order

Order this plain blind rivet nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1330A3-166> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.