

**Description**

thread: 10-32, keyed grip range: 0.065" - 0.116", countersunk head, aluminum alloy

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[MS27130-A99K](#) [MS27130A99K](#)

SKU / Model:	NAS1330A3K116
Minimum Qty (MOQ):	25
NSN:	5310-00-714-5971
ECCN:	EAR99
National Motor Freight:	013540, Alum Nuts



## P/N NAS1330A3K116 Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Head Style:</b>	Flat Countersunk Reverse Keyed
<b>Head Diameter:</b>	0.391 Inches Nominal
<b>Key Length:</b>	0.065 Inches Nominal
<b>Head Height:</b>	0.065 Inches Nominal
<b>Nut Style:</b>	Blind Rivet W/smooth Round Shank
<b>Nut Diameter:</b>	0.250 Inches Nominal
<b>Nut Length:</b>	0.578 Inches Nominal
<b>Err Default:</b>	+0.065/+0.116 Inches
<b>Unable To Decode:</b>	+0.065 To 0.116 Inches
<b>Shank End Type:</b>	Open
<b>Thread Series:</b>	Unf
<b>Thread Quantity Per Inch:</b>	32
<b>Nominal Thread Size:</b>	0.190 Inches
<b>Head Countersink Angle:</b>	100.00 Degrees Nominal
<b>Material:</b>	Aluminum Alloy Overall
<b>Surface Treatment:</b>	Anodize Overall
<b>Specification/standard Data:</b>	80205-nas1330 Professional/industrial Association Standard

## How to Order

Order this plain blind rivet nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1330A3K116> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.