

Description

thread: 10-32, keyed grip range: 0.065" - 0.116", countersunk head, aluminum alloy

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[MS27130-A99K](#) [MS27130A99K](#)

SKU / Model:	NAS1330A3K116
Minimum Qty (MOQ):	25
NSN:	5310-00-714-5971
ECCN:	EAR99
National Motor Freight:	013540, Alum Nuts



P/N NAS1330A3K116 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Head Style:	Flat Countersunk Reverse Keyed
Head Diameter:	0.391 Inches Nominal
Key Length:	0.065 Inches Nominal
Head Height:	0.065 Inches Nominal
Nut Style:	Blind Rivet W/smooth Round Shank
Nut Diameter:	0.250 Inches Nominal
Nut Length:	0.578 Inches Nominal
Err Default:	+0.065/+0.116 Inches
Unable To Decode:	+0.065 To 0.116 Inches
Shank End Type:	Open
Thread Series:	Unf
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.190 Inches
Head Countersink Angle:	100.00 Degrees Nominal
Material:	Aluminum Alloy Overall
Surface Treatment:	Anodize Overall
Specification/standard Data:	80205-nas1330 Professional/industrial Association Standard

How to Order

Order this plain blind rivet nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1330A3K116> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.