

P/N NAS1330A3K216

Description

Thread Size: 3/16", Nut Length: 5/8", flat countersunk reverse keyed head, fine thread, NAS1330 series nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1330A3K216
Minimum Qty (MOQ):	25
NSN:	5310-00-714-5966
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013540 Alum Nuts



^{*} See page 2 for technical characteristics

P/N NAS1330A3K216 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Head Style:	Flat Countersunk Reverse Keyed
Head Diameter:	0.391 Inches Nominal
Key Length:	0.065 Inches Nominal
Head Height:	0.065 Inches Nominal
Nut Style:	Blind Rivet W/smooth Round Shank
Nut Diameter:	0.250 Inches Nominal
Nut Length:	0.687 Inches Nominal
Err Default:	+0.166/+0.216 Inches
Unable To Decode:	+0.166 To 0.216 Inches
Shank End Type:	Open
Thread Series:	Unf
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.190 Inches
Head Countersink Angle:	100.00 Degrees Nominal
Material:	Aluminum Alloy Overall
Surface Treatment:	Anodize Overall
Specification/standard Data:	80205-nas1330 Professional/industrial Association Standard

How to Order

Order this rivnut from our inventory online by visiting https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1330A3K216 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.