

Description

Thread Size: 3/16", Nut Length: 47/64", rivnut

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|-------------------|
| SKU / Model: | NAS1330A3K266 |
| Minimum Qty (MOQ): | 20 |
| NSN: | 5310-01-163-8255 |
| Schedule B: | 7616.10.3000 |
| ECCN: | EAR99 |
| National Motor Freight: | 013540, Alum Nuts |



* See page 2 for technical characteristics

P/N NAS1330A3K266 Specifications

| | |
|---|--|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Head Style: | Flat Countersunk Reverse Keyed |
| Head Diameter: | 0.391 Inches Nominal |
| Key Length: | 0.065 Inches Maximum |
| Head Height: | 0.065 Inches Maximum |
| Nut Style: | Blind Rivet W/smooth Round Shank |
| Nut Diameter: | 0.246 Inches Minimum And 0.250 Inches Maximum |
| Nut Length: | 0.719 Inches Minimum And 0.749 Inches Maximum |
| Err Default: | +0.216/+0.266 Inches |
| Shank End Type: | Open |
| Thread Series: | Unf |
| Thread Quantity Per Inch: | 32 |
| Nominal Thread Size: | 0.190 Inches |
| Head Countersink Angle: | 99.0 Degrees Minimum And 100.0 Degrees Maximum |
| Material: | Aluminum Alloy 6063 Overall |
| Material Document And Classification: | Qq-a-200/9 Fed Spec Single Material Response Overall |
| Surface Treatment: | Anodize Overall |
| Surface Treatment Document And Classification: | Mil-a-8625,ty 2 Mil Spec Single Treatment Response Overall |
| Specification/standard Data: | 80205-nas1330 Professional/Industrial Association Standard |

How to Order

Order this plain blind rivet nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1330A3K266> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.