

Description

Thread Size: 3/16", Nut Length: 7/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1330A3KB166
Minimum Qty (MOQ):	10 EA
NSN:	5310-00-995-6712
Schedule B:	7616.10.3000
ECCN:	9A991
National Motor Freight:	013540, Alum Nuts



\* See page 2 for technical characteristics

## P/N NAS1330A3KB166 Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Head Style:</b>	Flat Countersunk Reverse Keyed
<b>Head Diameter:</b>	0.391 Inches Nominal
<b>Key Length:</b>	0.065 Inches Nominal
<b>Head Height:</b>	0.065 Inches Nominal
<b>Nut Style:</b>	Blind Rivet W/smooth Round Shank
<b>Nut Diameter:</b>	0.250 Inches Nominal
<b>Nut Length:</b>	0.875 Inches Nominal
<b>Err Default:</b>	+0.116/+0.166 Inches
<b>Shank End Type:</b>	Closed
<b>Thread Series:</b>	Unf
<b>Thread Quantity Per Inch:</b>	32
<b>Nominal Thread Size:</b>	0.190 Inches
<b>Head Countersink Angle:</b>	100.00 Degrees Nominal
<b>Material:</b>	Aluminum Alloy 6053 Overall
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Anodize Overall
<b>Specification/standard Data:</b>	80205-nas1330 Professional/industrial Association Standard

## How to Order

Order this rivnut from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1330A3KB166> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.