

Description

Thread Size: 1/4", Nut Length: 13/16"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1330A4K271
Minimum Qty (MOQ):	5 EA
NSN:	5310-01-150-8736
Schedule B:	7616.10.3000
ECCN:	9A991
National Motor Freight:	013540, Alum Nuts

NO IMAGE
AVAILABLE

P/N NAS1330A4K271 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Head Style:	Flat Countersunk Reverse Keyed
Head Diameter:	0.529 Inches Nominal
Key Length:	0.089 Inches Maximum
Head Height:	0.089 Inches Maximum
Nut Style:	Blind Rivet W/smooth Round Shank
Nut Diameter:	0.328 Inches Minimum And 0.332 Inches Maximum
Nut Length:	0.797 Inches Minimum And 0.827 Inches Maximum
Err Default:	+0.211/+0.271 Inches
Shank End Type:	Open
Thread Series:	Unf
Thread Quantity Per Inch:	28
Nominal Thread Size:	0.250 Inches
Head Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Aluminum Alloy 6053 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625,ty 2 Mil Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1330 Professional/Industrial Association Standard

How to Order

Order this rivnut from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1330A4K271> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.