

Description

Thread Size: 7/64", Nut Length: 13/32

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1330C04K106
Minimum Qty (MOQ):	5
NSN:	5310-00-438-3649
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,



P/N NAS1330C04K106 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Head Style:	Flat Countersunk Reverse Keyed
Head Diameter:	0.263 Inches Nominal
Key Length:	0.051 Inches Maximum
Head Height:	0.051 Inches Maximum
Nut Style:	Blind Rivet W/smooth Round Shank
Nut Diameter:	0.151 Inches Minimum And 0.155 Inches Maximum
Nut Length:	0.380 Inches Minimum And 0.410 Inches Maximum
Err Default:	+0.081/+0.106 Inches
Unable To Decode:	+0.081 To 0.106 Inches
Shank End Type:	Open
Thread Series:	Unc
Thread Quantity Per Inch:	40
Nominal Thread Size:	0.112 Inches
Head Countersink Angle:	99.00 Degrees Minimum And 100.00 Degrees Maximum
Material:	Steel Comp 430 Overall
Material Document And Classification:	Qq-w-423,form 1 Fed Spec Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35,ty 2 Fed Spec Single Treatment Response Overall

How to Order

Order this plain blind rivet nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1330C04K106> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.