

Description

Thread Size: 7/64", Nut Length: 27/64"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1330C04K131
Minimum Qty (MOQ):	10 EA
NSN:	5310-00-922-6331
Schedule B:	7318.16.0085
ECCN:	9A991
National Motor Freight:	077140, Fruits Dried / Evaporated Noi

NO IMAGE
AVAILABLE

P/N NAS1330C04K131 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Head Style:	Flat Countersunk Reverse Keyed
Head Diameter:	0.263 Inches Nominal
Key Length:	0.051 Inches Nominal
Head Height:	0.051 Inches Nominal
Nut Style:	Blind Rivet W/smooth Round Shank
Nut Diameter:	0.151 Inches Minimum And 0.155 Inches Maximum
Nut Length:	0.405 Inches Minimum And 0.435 Inches Maximum
Err Default:	+0.106/+0.131 Inches
Shank End Type:	Open
Thread Series:	Unc
Thread Quantity Per Inch:	40
Nominal Thread Size:	0.112 Inches
Head Countersink Angle:	100.00 Degrees Nominal
Material:	Steel Comp 430 Overall
Material Document And Classification:	Qq-w-423,form 1 Fed Spec Single Material Response Overall
Surface Treatment:	Passivate Overall

How to Order

Order this rivnut from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1330C04K131> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.